



US007704388B2

(12) **United States Patent**
Chi et al.

(10) **Patent No.:** **US 7,704,388 B2**
(45) **Date of Patent:** **Apr. 27, 2010**

(54) **REUSABLE LIQUID CHROMATOGRAPHIC COLUMNS**

(75) Inventors: **Yawu Chi**, Sharon, MA (US); **Lixin Cao**, Princeton, NJ (US); **Ying Xu**, Edison, NJ (US)

(73) Assignee: **Luknova, Inc**, Princeton, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 737 days.

(21) Appl. No.: **11/307,312**

(22) Filed: **Jan. 31, 2006**

(65) **Prior Publication Data**

US 2007/0175809 A1 Aug. 2, 2007

(51) **Int. Cl.**
B01D 15/08 (2006.01)

(52) **U.S. Cl.** **210/198.2**; 210/232; 210/282; 210/656

(58) **Field of Classification Search** 210/198.2, 210/635, 656, 232, 238, 282; 96/101, 105, 96/106; 95/82

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,483,986	A *	12/1969	Wright	210/198.2
4,565,632	A *	1/1986	Hatch et al.	210/656
4,876,005	A *	10/1989	America	210/198.2
5,342,515	A *	8/1994	Radmacher	210/198.2
5,601,708	A	2/1997	Leavesley	210/198.2
5,716,525	A *	2/1998	Nickerson	210/634

6,325,929	B1 *	12/2001	Bassett	210/238
6,358,414	B1 *	3/2002	Maiefski	210/198.2
6,423,220	B1	7/2002	Fex	210/198.2
6,436,284	B1	8/2002	Leavesley et al.	210/198.2
6,458,273	B1 *	10/2002	Krakover et al.	210/198.2
6,565,745	B2	5/2003	Hodgin et al.	210/198.2
6,692,556	B2 *	2/2004	Hayes et al.	96/147
6,736,973	B1 *	5/2004	Podgornik et al.	210/656
6,797,174	B2	9/2004	Neuroth	210/656
6,811,688	B1	11/2004	Hofmann	210/198.2
6,949,194	B2	9/2005	Hodgin et al.	210/656
2002/0008058	A1 *	1/2002	Nugent	210/198.2
2004/0129624	A1 *	7/2004	Hamlin et al.	210/315
2005/0133426	A1 *	6/2005	DeMarco	210/198.2
2005/0242018	A1 *	11/2005	Hodgin et al.	210/198.2
2006/0207939	A1 *	9/2006	Allington et al.	210/656
2007/0163102	A1 *	7/2007	DeMarco	29/525.14


* cited by examiner

Primary Examiner—Ernest G Therkorn
(74) *Attorney, Agent, or Firm*—Steven N. Fox

(57) **ABSTRACT**

A reusable liquid chromatographic column consists of three parts, a column body with an integral outlet port molded on one end, a sealing insert with an inlet port, and a perforated cap providing downward force to compress the sealing insert into the column body. A wedge-like seal is employed to seal the connection between the sealing insert and the column body. Two filters on both ends of the column body are used to prevent escape of packing materials from the column chamber under pressure. Hand tightening is adequate to seal the connection by screwing the perforated cap onto the column body. The column is reusable due to its simple disassembling and reassembling processes. It is also disposable due to its inexpensive fabricating materials and manufacturing process.

5 Claims, 7 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

REUSABLE LIQUID CHROMATOGRAPHIC COLUMNS

BACKGROUND OF THE INVENTION

The invention relates to liquid chromatographic columns and methods of assembling and disassembling reusable, economic, and leak-free chromatographic columns.

Liquid chromatography is an analytical chromatographic technique that is based on differences in partitioning behaviors between a mobile phase and a stationary phase to separate the components in a mixture, more specifically, to separate ions or molecules dissolved in a solvent. A column is packed with the stationary phase and the mobile phase carries the mixture through it. Sample components having stronger affinity with the stationary phase spend longer time in the column and are separated from components that have weaker affinity with the stationary phase and pass through the column faster.

In pursuit of optimal separation, the chromatography system is usually operated under pressure to facilitate the flow of the mobile phase in the stationary phase. As a consequence, the columns demand effective seals to prevent the mobile phase from leaking out of the pressurized passage. An O-ring employed in some prior art methods (U.S. Pat. No. 5,601,708 and U.S. Pat. No. 6,436,284) can provide a good seal for the openings of the column, but some organic solvents used as a mobile phase in liquid chromatography can damage the O-ring after a lengthy soaking in the solvents. The methods for making commercially available disposable columns (U.S. Pat. Nos. 6,565,745 and 6,949,194) involve the use of a snap-on cap to form a sealing connection between the column body and the sealing head. This technique could lead to sealing failure under substantial pressure build-up. In addition, the use of snap-on cap with cantilever members and the ramped detents molded on the column body forms a tight interference fit, which practically makes the column solely for one-time use due to the inability in disassembling column for repeated uses. Columns made of glass (U.S. Pat. No. 6,811,688) cannot withstand a pressurized system and cost more than plastic columns. Other prior art technique (U.S. Pat. No. 6,797,174) requires a complicated process involving six separate pieces and one spacer ring. A low-pressure liquid chromatographic cartridge is provided with a resilient fluid tight seal (US Patent Application 2005/0247632), but the rotation resulted from threading the cap onto the cartridge container could cause seal failure and the cartridge is not reusable.

All these prior art techniques have the drawbacks of high cost for column assembly, seal failure, or one-time use. It is the object of this invention to provide reusable, economic, and leak-proof liquid chromatographic columns for the separation and purification of organic compounds.

SUMMARY OF THE INVENTION

The invention is aimed at providing reusable, economic and leak-proof liquid chromatographic columns. It is still aimed at providing a simple, but reliable process to assemble and disassemble the columns. In one aspect, the columns can be reusable since the assembly and disassembly processes are easy to fulfill without assistance from special devices or machines. Conventional tools, such as pliers, wrenches, and tweezers, are adequate to disassemble and assemble the columns. In another aspect, the columns are also disposable due to its inexpensive materials and simple assembly process.

The column includes three separate parts, a cylindrical body with one end having one port molded as a single piece to the body and the other end with an opening for loading the packing material and sealing, a sealing insert molded with another port directed toward the body chamber, and a perforated

rated cap used to force the sealing insert into the column body by use of hand-tightening. At the both ends of the packing material loaded in the column chamber, two filters are employed to prevent the packing material from entering the ports.

In the preferred embodiment, a wedge-like seal is adopted to the connection between the column body with a tapered rim on the inner wall and the sealing insert with a conical circumference. The outer wall on the opening portion of the column body is molded with male threads for the perforated cap comprising female threads. The sealing insert, along with the perforated cap around it, is placed into the column body. By turning the cap onto the column base, the perforated cap provides straight downward force to push the sealing insert into the column body to form a compression type fitting. The perforated cap has small ridges on the outer wall to aid in gripping and hand-tightening with ease.

One of the advantages and features of this invention is the column designed for repeated uses. Although the used column is disposable, it can afford multiple uses with appropriate disassembling and reassembling processes. The used column is readily disassembled by unscrewing the perforated cap, pulling out the sealing insert, and then removing filters and the packing material. After reloading with new packing material and filters into the used column body, the used sealing insert and perforated cap are reassembled onto the column body to form a new column with tight seal. A column in this embodiment can be reused up to ten times, preferably two to three times with replacement of new packing material and filters each time. The number of using times is subject to the integrity of the sealing interface between the sealing insert and the column body. A smooth surface free of cracks or niches is indispensable for the column reassembly. The invented liquid-chromatographic columns can sustain relatively high pressure up to 180 psi.

The column may also be disposable thanks to its inexpensive fabricating material, such as polyethylene, polypropylene, and its economic assembling process. Packing materials include silica, silica gel, alumina, regenerated silica, regenerated silica gel, regenerated alumina, and the like. Hand-tightening without or with slight assistance from wrenches or pliers is sufficient to provide reliable seal under substantial internal pressure. Other advantages of this invention will be described in the preferred embodiment thereof and from the claims.

DESCRIPTION OF THE DRAWINGS

For the purpose of easy understanding the advantages this invention brings, the following seven drawings are used to explicitly describe the column features and the assembling and disassembling processes.

FIG. 1 is a perspective view of the whole column based on this invention;

FIG. 2 is an exploded cross-sectional view of the column of FIG. 1;

FIG. 3 is a fragmentary sectional view of the sealing part;

FIG. 4 is a perspective view of the sealing insert (Type I);

FIG. 5 is a cross-sectional view of the sealing insert of FIG. 4;

FIG. 6 is a perspective view of the sealing insert (Type II); and

FIG. 7 is a perspective view of the perforated cap.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 shows a perspective view of the whole column in this embodiment. The chromatographic column 10 with a

cylindrical structure has a sealing insert **18** with a molded inlet port **14**, a perforated cap **20**, and a column body **12** with a molded outlet port **16**. The packing material is loaded inside the column chamber **13**. In the operation procedure, the inlet port **14** is connected to a source where the mobile phase flows into the column **10**. The mobile phase carries mixture from the inlet port **14** to outlet port **16** through the packing material in which components are separated due to different retention times caused by the difference in affinity of each component to the packing material. The outlet port delivers the separated components to a detecting device to identify or quantify each component, which is finally collected in containers. The size of the column **10** varies with the amount of separated samples.

Referring to FIG. 2, it is seen that the column **10** has five pieces in sequence: a perforated cap **20** with an opening **56**, a sealing insert **18** with an inlet port **14**, an inlet filter **22**, an outlet filter **24**, and a column body **12** molded with an outlet port **16**. The cylindrical chamber **13** is for filling the packing material, such as silica gel. Two filters **22** and **24**, porous frit, are placed on the two ends of the column chamber **13** to avoid the leaks of the packing material from the column body **12**. The inlet port **14** is integrally molded on the sealing insert **18**, which is placed into the open end of the column body in the assembling process. A perforated cap **20** with female threads **54** is used to fix the sealing insert **18** into the column body **12** with a sealing connection.

The sealing connection of the apparatus is shown in FIG. 3. The wedge-like seal is used to form a tight seal at the inlet end. The inlet opening of the column body **12** consists of a tapered end **26**, which receives a slope **36** on the sealing insert **18** to form the sealing surface. The perforated cap **20** is placed onto the sealing insert **18** to provide downward force to push the sealing insert **18** into the column body **12** by screwing down the perforated cap onto the column body. In this sealing connection, the perforated cap **20** with female threads **54** plays a role as a nut with female threads and the column body **12** is like a hollow bolt with male threads **28** on the outer wall. The sealing insert **18** is forced to move linearly downward into the column body **12** without tangential rotating movement. A compression-type fitting is formed between the slope **36** of the sealing insert **18** and the tapered rim **26**. The use of threads in the connection allows easy disconnection of the perforated cap **20**, the sealing insert **18**, and the column body **12** without damaging the sealing interface. The outer diameter of the step **44** of the sealing insert **20** is sized to fit within the perforation opening **56** of the perforated cap **20** with minimum radial clearance of 0.01 mm to 10 mm between the two. The clearance leads to easy operation and avoids tangential rotating movement between the sealing insert **18** and the tapered end **26** during the cyclic operation of assembly, disassembly, and reassembly. The design aimed at easy disassembly and reassembly of the column provides a base for reusing the column with multiple times.

FIG. 4 shows a conventional design (Type-I) for the insert **18**. The inlet port **14** has a female luer fitting with partial male threads **40** to connect to a source where the mobile phase flows through. Finger-tightening is adequate to connect the inlet port to the source of the mobile phase by turning the fitting on. Referring to FIG. 5, the radius of the circumferential stair **32** is extended to be a little larger than the inner radius of the opening of the column body **12** in avoidance of the whole sealing insert **18** entering the column body **12**. A side slope **36** with an angel from 5 to 75°, preferably from 10 to 50°, mating the surface of the tapered end **26** allows the sealing insert **18** to slide into the column body **12**. Three stairs **38**, **42** and **44** are employed to reinforce the hardness and mechanical strength of the inlet port. Although the stairs with

other numbers of more than three or less than one (no stair) can be used, two to three stairs are preferred in the invention for repeated uses. The height of the stair **38** is equal to the height of the circumferential stair **32** in order to receive even downward force in the center and on the edge of the sealing insert **18**. The use of the recess **46** between stair **38** and **32** is aimed at saving materials and avoiding the insert deformation caused by thick layer in the molding process.

As shown in FIG. 5, a conical shape **48**, which is open toward the inlet filter **22** at the end the inlet passage, is designed to allow even dispersion of fluid cross the filter **22** and the packing materials in the column body **12**. The sealing insert **18** has an additional circular protrusion **50** on the rim of the insert bottom **51**. The protrusion with a height of 1.5 mm (e.g. 0.5 to 5 mm, preferably 1 to 3 mm) has a 75° angel (e.g. 30 to 150°, preferably 60 to 120°) in section and protrudes downward from the surface **51**. After compressed downward, the protrusion **50** can dig into the filter **22**, which is tightly against the walls of the column body **12** to stop the movement of packing materials under pressure, to form a seal in case that any defect fitting between the filter **22** and the column wall cause the leaks of the packing material. Accordingly, another protrusion **25** with the size equal to the protrusion **50** is positioned against the filter **24** at the outlet end to prevent leaks of the packing material to the outlet port **16**. The disk-shaped filters **22** and **24** are made of porous polymer with elasticity for receiving pressing from the protrusions **50** and **25**, respectively.

An alternative design (Type-II) for the sealing insert is shown in FIG. 6. The sealing insert **19** has radial spokes **45A-45F** with a number of 6 (e.g. 2 to 16, preferably 4 to 12). The spokes **45A-45F** molded on the bottom **43** of the sealing insert **19** are used to increase the mechanical strength of the bottom **43** and enable the bottom to withstand substantial internal pressure. The spoke height is lower than that of the circumferential step **41**. The spokes **45A-45F** are extended from the stair **39** outwardly, but not reach to the wall of the circumferential step **41**. The space between the end of each spoke and the wall is intended to make the sealing slope receive the even force from the tapered rim **26**. Stairs **37** and **39** are used to reinforce the mechanical strength of the inset port **14**. This spoke-molded insert is preferably designed for a big size column, which has a large contact surface between the sealing insert and the filter **22**. The bottom surface **43** integrated with spokes of the sealing insert **19** can prevent deformation under high internal pressure. The radial spokes can also be employed to increase the mechanical strength of the bottom **58** at the outlet of the column body **12** for the sake of high internal pressure tolerance.

The compressive force applied to pushing the sealing insert **18** downward is provided from the perforated cap **20** by screwing it onto the column body **12**. FIG. 7 shows the perspective view of the perforated cap **20**, which functions as a nut with female threads **54**. The knurls **52**, regular small ridges on the outer surface of the perforated cap **20**, assist to prevent slipping while the connection is tightened by hands through gripping the perforated cap **20**. Referring to the cross-sectional view of the column **10** in FIG. 2, female threads **54** along with male threads **28** on the outer wall of the column body **12** can be clockwise or counter-clockwise. A perforation **56** sized between the diameters of the stair **44** and the stair **38** is formed on the top of the cap **20** to ensure that the downward force is evenly scattered on the stairs **32** and **38** of the insert **18**. The connection with separate sealing insert **18** and perforated cap **20** provides only straight linear movement between the slope **36** and the tapered end **26** instead of tan-

5

gential movement, which can cause abrasion and defects at the sealing interface and eventually give rise to a failed seal.

In the packing process of a chromatographic column, the filter 24 with the diameter equal to the bottom size of the column body 12 is firmly placed against the protrusion 25. The packing materials are introduced to the column chamber 13 with the assistance of vacuum hooked to the outlet port, or just by vibrating the column body 12 to ensure the packing materials closely packed inside the column chamber. Any void volume in the packing materials should be prohibited since it can lead to poor separation efficiency. After the packing material nearly reaches to the tapered end 26, the inlet filter 22 is placed on the top of the packing material layer. The sealing insert 18 is then inserted into the tapered end 26. Once the perforated cap 20 is aligned onto the sealing insert 18, the connection can be firmly formed by turning the perforated cap 20 onto the column body 12. A wrench or a pair of pliers may be applicable to aiding tightening, but hand tightening is adequate to assemble the column with tight seal.

The column allows a number of repeated uses since it can be easily disassembled and reassembled with hands. After the packing material in the used column is dry, the perforated cap 20 is readily unscrewed from the column body 12. The filters 22 and 24, as well as the packing material, are then removed from the column chamber 13. Three parts including the perforated cap 20, the sealing insert 18, and the column body 12, can be cleaned with organic solvents for the next use. With replacement of the packing material and two filters, a new column can be easily reassembled according to the assembling process described above. During the assembling and disassembling process, the contact surfaces of the tapered end 26 and the slope 36 should be kept clean, smooth, and free of any cracks or niches. The column can be used up to ten times with care of three reusable parts, the perforated cap 20, the sealing insert 18, and the column body 12.

In this design, the sealing connection consisting of the sealing insert 18 and the perforated cap 20 performs as an inlet end, as described above. However, in the preferred embodiment, the inlet port 14 and outlet port 16 can switch positions if the female luer fitting with partial male threads 40 is molded on the column end 16. As a consequence, the sealing connection would be on the outlet end. The mobile phase would flow into the column through the molded end and flow out of the column through the sealing connection end. Indeed, such an upside-down design would enhance the column resistance against leaks under a pressurized system since the outlet pressure is always lower than the inlet pressure. The preferred embodiments and illustrative details set forth should merely be regarded as descriptive disclosure. Various other changes and additions in the form and detail thereof may be made therein without departing from the spirit and scope of the invention.

In one embodiment, the device comprises a one-piece reusable plastic tubular body comprising a first open end having an inside diameter ID1. The body further comprises external threads disposed about the first open end. The body further comprises tapered rim disposed at the first open end.

The device further comprises a sealing insert comprising a stem extending upward from the base. The stem comprises first and second annular stairs, and an inlet port. The first annular stair has an outside diameter OD1. The second annular stair has an outside diameter OD2. The outside diameter OD1 of the first annular stair is larger than the outside diameter OD2 of the second annular stair. The stem further comprises a third annular stair disposed above the second annular stair. The third annular stair has an outside diameter OD3. The outside diameter OD2 of the second annular stair is larger

6

than the outside diameter OD3 of the third annular stair. The first annular stair has a height H1 relative to the top surface of the base. The annular wall surrounds the first annular stair of the stem. The annular wall is substantially spaced apart from the first annular stair to form an annular recessed portion with the top surface. The annular wall comprises an upper annular end, an annular sloped surface, and a lower annular protrusion. The upper annular end of the annular wall has a height H2 relative to the top surface of the base. The height H1 of the first annular stair is equal to the height H2 of the upper annular end of the annular wall. The sealing insert further comprises an annular wall disposed at the perimeter of the base. The upper annular end of the annular wall has an outside diameter OD4 that is larger than the inside diameter ID1 of the first open end of the tubular body.

The device further comprises a one-piece reusable plastic cap comprising a top wall, a central opening disposed in the top wall, and an annular sidewall having internal threads removably engaged with the external threads of the tubular body. The inlet port of the stem passes that the central opening and extends outward of the top wall of the cap. The central opening has an inside diameter ID2. The inside diameter ID2 of central opening is less than the outside diameter OD1 of the first annular stair.

What is claimed is:

1. A reusable chromatographic device comprising:

a one-piece reusable plastic tubular body comprising a first open end having an inside diameter ID1; said body further comprises external threads disposed about said first open end; said body further comprises a tapered rim disposed at said first open end;

a one-piece reusable plastic sealing insert comprising a circular base having a perimeter portion; said sealing insert further comprising substantially planar top and bottom surfaces; said sealing insert further comprising a stem extending upward from said base; said stem comprises first and second annular stairs, and an inlet port; said first annular stair has an outside diameter OD1; said second annular stair has an outside diameter OD2; said outside diameter OD1 of said first annular stair is larger than said outside diameter OD2 of said second annular stair; said first annular stair has a height H1 relative to said top surface of said base; said sealing insert further comprises an annular wall disposed at said perimeter of said base; said annular wall surrounds said first annular stair of said stem; said annular wall is substantially spaced apart from said first annular stair to form an annular recessed portion; said annular wall comprises an upper annular end, an annular sloped surface, and a lower annular protrusion; said upper annular end of said annular wall has a height H2 relative to said top surface of said base; said height H1 of said first annular stair is equal to said height H2 of said upper annular end of said annular wall; said upper annular end of said annular wall has an outside diameter OD4 that is larger than said ID1 of said first open end of said tubular body;

a one-piece reusable plastic cap comprising a top wall, a central opening disposed in said top wall, and an annular sidewall having internal threads removably engaged with said external threads of said tubular body; said inlet port of said stem passes thru said central opening and extends outward of said top wall of said cap; said central opening has an inside diameter ID2; said inside diameter ID2 of central opening is less than said outside diameter OD1 of said first annular stair; and

rotation of said cap causes said top wall of said cap to apply a straight downward force upon said upper annular end

7

and said first annular stair of said stem, respectively, of said sealing insert; and said rotation of said cap further causes said annular sloped surface of said sealing insert to form a seal with said tapered rim of said first open end of said tubular body.

2. The device of claim 1, wherein said stem further comprises a third annular stair disposed above said second annular stair; said third annular stair has outside diameter OD3; said outside diameter OD2 of said second annular stair is larger than said outside diameter OD3 of said third annular stair.

8

3. The device of claim 2, wherein said annular sloped surface has an angle in the range of 10 to 50 degrees.

4. The device of claim 3, wherein said lower annular protrusion of said annular wall has a height in the range of 1 mm to 3 mm relative to said bottom surface of said base.

5. The device of claim 4, wherein said lower annular protrusion of said annular wall has an angle in the range of 60 to 120 degrees.

* * * * *